

## ARMORWELD® Plumbers Pal Soldering Pad

HIGH TEMPERATURE CARBON PAD  
up to 4000° F

### PRODUCT DATA SHEET

- **Withstands** direct flames, heavy sparks, and molten solder
- **Prevents** the transfer of damaging heat to wood, drywall or fixture
- **Resists** tearing and fraying
- **Packs** into voids or openings
- **Protects** delicate surfaces and finishes from abrasion
- **Releases** residual slag or solder easily after cooling
- **Re-usable** many times over
- **Health** friendly
- **Grommets** for ease of hanging



Please note: Armorweld® Carbon Felt should not come in contact with direct oxygen enhanced flame. Unspent oxygen combined with heat can oxidize any carbon fiber. Consult customer service for application compatibility.

### Technical Specifications:

**Construction:** 100% Pre-Ox Pan Carbon Fiber

**Thickness:** 0.180 – 0.220 Nominal

**Weight:** 14.9 oz./sq. yard nominal

**Temperature:** Excursions to 4000° F. in non-oxidizing environments

**Available Sizes:** 9" X 12", 12" X 12" & 18" X 18"

Sold 12 pcs. per case

### Plumbers Pal

Part Number	Fabric Weight	Nominal Width	Nominal Length
PPCF22-9X12	15oz. nom.	9"	12"
PPCF22-12X12	15 oz. nom.	12"	12"
PPCF22-18X18	15 oz. nom.	18"	18"